



000 «Полимер Экспорт»

ПРОМЫШЛЕННЫЕ ЛАКОКРАСОЧНЫЕ ПОКРЫТИЯ

8 (4932)773-503

raum-profile.ru
Inmarketing@gk-rp.ru



Release date: 01.08.2020

Manufacturer: Russian Federation

PAINT AK-511 FOR CONCRETE FLOOR

ТУ 2313-011-20514586-2006

СЕРТИФИКАЦИЯ

State Registration Certificate № RU.37.ИЦ.02.015.E.000007.02.12 from 22.02.2012.

DESCRIPTION

Fast drying solvent-based acrylic paint.

FIELDS OF APPLICATION

Acrylic paint is applied to asphalt or concrete and forms matt coating. The paint is also used to line roads, parking lots, children's and sports grounds as well as for surfaces exposed to high loads. Provides fast drying, excellent adhesion to concrete, high abrasion resistance. The coating is resistant to water, sharp temperature changes, withstands temperatures from -45°C to +45°C.

TECHNICAL DATA

Colour	White, grey, yellow Other colours due to customer need
Mass fraction of dry residue	70 ± 3%
Open time to grade 3 at (20±2)°C and air humidity no more 65 %, no more	40 min
Coating thickness, no more	200 microns
Consumption	One layer consumption is 300-500 g/m ² depending on colour, surface condition and application method.

INSTRUCTION FOR USE

Well-bottomed dry clean surface must be free of grease and dust. To improve concrete base and adhesion, the surface must be coated with primer AK-027 «RAUM-PROFIE».

CONDITIONS

Ambient temperature must be from +5°C to +25°C.
Air humidity no more than 80%.

APPLICATION

Preparing	Mix before to use. Thin with thinner P-4 to painting consistency if needed.
Brush	Use to coat
Roller	Use to coat

PACKAGE SIZE

Metal euro bucket 21l: basis 28 kg.

STORAGE

Store in a tightly closed container in a dry room, away from sources of ignition, protecting from direct sunlight and moisture.

GUARANTED STORAGE LIFE

Expire date is 12 months in case if delivery and storing rules are followed. After expire date shouldn't be used without tests.

HEALTH AND SAFETY

When painting work, use personal protective equipment (respirators, gloves, glasses, etc.). Work inside the room should be carried out with artificial (local, general) or natural ventilation. Use the primer only in places without sources of open fire and ignition. Avoid contact with skin or eyes. In case of skin contact immediately wipe with a rag or cotton swab, rinse thoroughly with soapy water, do not use solvents. In case of eyes contact rinse with



Собственное современное производство



Система Менеджмента Качества (ISO 9001)



Аттестованная лаборатория



На рынке с 2002 года



ООО «Полимер Экспорт»
ПРОМЫШЛЕННЫЕ ЛАКОКРАСОЧНЫЕ ПОКРЫТИЯ

 **8 (4932)773-503**

 **raum-profile.ru**
lnmarketing@gk-rp.ru



clean water for at least 10 minutes, consult a doctor. In case of ingestion, consult a doctor.

RECYCLING

Packing materials are recycled as consumer waste.

Further Information.

The recommendations above are based on our own research and our best knowledge but don't fully guarantee any particular case as it depends on the quality, friability and porosity of the base. The local working conditions and methods may vary and are beyond our control. Therefore we cannot be held responsible for the actual work on the site. The information is currently updating.



Собственное
современное
производство



Система
Менеджмента
Качества
(ISO 9001)



Аттестованная
лаборатория



На рынке
с 2002 года