



ООО «Полимер Экспорт»

ПРОМЫШЛЕННЫЕ ЛАКОКРАСОЧНЫЕ ПОКРЫТИЯ

8 (4932)773-503



raum-profile.ru  
Inmarketing@gk-rp.ru



Release date: 01.08.2025

Manufacturer: Russian Federation

TC 20.30.22-005-69372620-2020

## FORMULA THINNER «Polytex Slow»

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| CERTIFICATE             | State Registration Certificate № RU.01.PA.02.008.E.000800.06.22 от 10.06.2022 г<br>MSDS № 69372620-20.30-0103 от 10.10.2023 г.                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                        |
| DESCRIPTION             | General purpose thinner for «Polytex» products when hot drying.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                        |
| FIELDS OF APPLICATION   | It is used for thinning two-component polyurethane materials, mainly where hot drying is required. The thinner contains a high-boiling fraction to contribute to good filling, high gloss and high-quality paint film formation, even at elevated temperatures. This thinner helps to avoid such surface defects as shagreen, punctures and prevent solvent popping during coating formation.<br>More detailed information for thinning can be found in products technical specifications.                                                                               |                                                                                                        |
| TECHNICAL DATA          | Colour and appearance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Transparent liquid, does not contain foreign impurities.                                               |
|                         | Mass fraction of water, %, no more                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0,05                                                                                                   |
|                         | Thinning action                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | No curdling or paint separation are allowed. No coat whitening and matt spots are allowed after drying |
|                         | Density at 20°C, g/cm <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0,890-0,910                                                                                            |
| PACKAGE SIZE            | Plastic can 10 l: 9kg/10 l.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                        |
| STORAGE                 | The material is stored in the original manufacturer packaging in closed warehouses at temperatures from - 40°C to + 40°C, away from sources of ignition. The material should be protected from mechanical damage, direct sunlight, precipitation, moisture penetration and condensation formation.                                                                                                                                                                                                                                                                       |                                                                                                        |
| GUARANTEED STORAGE LIFE | Expire date is 12 months in case if delivery and storing rules are followed. After expire date shouldn't be used without tests.                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                        |
| HEALTH AND SAFETY       | When painting work, use personal protective equipment (respirators, gloves, glasses, etc.). Work inside the room should be carried out with artificial (local, general) or natural ventilation. Use the thinner only in places without sources of open fire and ignition. Avoid contact with skin or eyes. In case of skin contact immediately wipe with a rag or cotton swab, rinse thoroughly with soapy water, do not use solvents. In case of eyes contact rinse with clean water for at least 10 minutes, consult a doctor. In case of ingestion, consult a doctor. |                                                                                                        |
| COMPOSITION             | Mixture of target thinners.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                        |
| RECYCLING               | Packing materials are recycled as consumer waste.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                        |

### Further Information.

The recommendations above are based on our own research and our best knowledge but don't fully guarantee any particular case as it depends on the quality, friability and porosity of the base. The local working conditions and methods may vary and are beyond our control. Therefore we cannot be held responsible for the actual work on the site. The information is currently updating.



Собственное  
современное  
производство



Система  
Менеджмента  
Качества  
(ISO 9001)



Аттестованная  
лаборатория



На рынке  
с 2002 года